



Fuse Probe Kit, Slim Front

Part Number:- 131597/Termination
 Features GS 38 Compliant.
 1.2 Metre Double Skin Silicone Cable. Bi-coloured layers.
 1.0mm² c.s.a. 3.6mm Ø Nom.o/d Multistranded very flexible copper core.
 Temp. Rating -10°C to +150°C
Fuse Rating: 500mA/1000V/50kA
 Packed in poly bag

IEC 61010 Rating.
 Measurement Category.
 Fused Probe Leads 1000V CAT III
 Current Rating. As Per Fuse
 Insulation Category. Double/Reinforced.
 Pollution Degree. Two (2)

Silvertronic confirm that the product(s) listed have been designed, manufactured and tested to and are therefore fully compliant to:

IEC 61010-0310-2015. (International CB Scheme).
EN 61010-31-2015. (European).
UL 61010-03, 2nd Edition. (United States).
CSA C22.2 No 61010-03, 2nd Edition (Canada).

All products marked as per IEC requirements. UL and CSA marking upon request.

All testing carried out by independent third party test house and CB Test Laboratory,

MET Laboratories Inc. Baltimore MD 21230 USA

The product(s) also meet the requirements of the Low Voltage Directive 2014/35/EU and where applicable comply with HSE GS.38.

