



1000V GS38 Compliant Fuse Probe Kit, Flat Blade Front

Part Number:-	131530/Termination
Features	GS 38 Compliant. 1.2 Metre Double Skin Silicone Cable. Bi-coloured layers. 1.0mm ² c.s.a. 3.6mm Ø Nom.o/d Multistranded very flexible copper core. Temp. Rating -10°C to +150°C <i>Fuse Rating: 500mA/1000V/50kA</i> Packed in poly bag
IEC 61010 Rating.	
Measurement Category.	1000V CAT III/600V CAT IV
Current Rating.	As Per Fuse
Insulation Category.	Double/Reinforced.
Pollution Degree.	Two (2)

Silvertronic confirm that the product(s) listed have been designed, manufactured and tested to and are therefore fully compliant to:

IEC 61010-031:2015. (International CB Scheme).
EN 61010-031:2015. (European).
UL 61010-031, 2nd Edition. (United States).
CSA C22.2 No 61010-031, 2nd Edition (Canada).

All products marked/labelled as per IEC requirements. UL and CSA labelling upon request.

All testing carried out by independent third party test house and CB Test Laboratory,

MET Laboratories Inc. Baltimore MD 21230 USA

The product(s) also meet the requirements of the Low Voltage Directive 2014/35/EU and where applicable comply with HSE GS.38.

